



Custom designed optic with optional, interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

- Material/Lens** Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Spring loaded clip with built in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One way valve for case venting. Available in international safety orange
- Dims/Weight** Height: 17.92 cm; Height in charger: 22.02 cm; Width: 7.24 cm; Diameter: 7.29 cm; Grip area: Height: 9.14 cm; Thickness: 3.43cm; Width: 5.59 cm  
Weight: 388g (with lithium rechargeable or AA alkaline); 354g (with AA lithium)
- Light Source** C4® LED technology, impervious to shock with a 50,000 hour lifetime  
Custom "Total Internal Reflection" optic for narrow beam and optimum peripheral illumination. Insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.
- Output/Run time** Four lighting modes:  
  - High for a super-bright beam that pierces through smoke: 41,000 candela; 175 lumens; 405m beam distance; runs 3.5 hours (lithium rech); runs 8 hours (AA alkaline or AA lithium)
  - Low for bright light and longer run time: 14,000 candela; 60 lumens; 237m beam distance; runs 10 hours (lithium rech); runs 20 hours (AA alkaline or AA lithium)
  - Flash for signaling: runs 5 hours
  - Moonlight mode provides low-level lighting for battery conservation: runs 15 days
- Switch** Rubber dome push-button actuator provides easy operation even when wearing heavy gloves
- Battery** NiMH/NiCd battery rechargeable up to 1,000 times; also accepts 4 "AA" alkaline batteries
- Features**
- Reduced bezel length to minimize snag hazards
  - Updated clip design for easy attachment on turnout gear
  - IPX4 water-resistant; 2m impact resistance tested
  - Super strong pocket clip
- Approvals** **ATEX/IECEX** FTZU 15 ATEX 0046X; IEC Ex FTZU 15.0029X  
II 1G Ex ia IIB T3/T4 Ga; II 2G Ex ia IIC T3/T4 Gb  
**InMetro** DNV 16.0014X  
Ex ia IIB T3/T4 Ga; Ex ia T3/T4 Gb
- Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

ITEM	UPC	ITEM #
Survivor - 230V AC/12V DC - Orange (ATEX)	080926-90562-7	90562
Survivor - 230V/12V DC - Orange (InMetro)	080926-90580-1	90580
Survivor - 240V AC/12V DC - Orange (ATEX)	080926-90563-4	90563
Survivor - 100V AC/12V DC - Orange (ATEX)	080926-90564-1	90564
Survivor - 12V DC Fast Charge - Orange (ATEX)	080926-90565-8	90565
Survivor - (WITHOUT CHARGER) - Orange (ATEX)	080926-90566-5	90566
Survivor - (WITHOUT CHARGER) - Orange (InMetro)	080926-90581-8	90581
Survivor Alkaline Model - Orange (InMetro)	080926-90582-5	90582
Survivor - Alkaline Model - Orange (ATEX)	080926-90567-2	90567



Item	UPC	Part #
DC2 direct wire charge cord	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051
100V/120V AC charge cord	080926-22060-7	22060
230V AC charge cord	080926-22061-4	22061
240V AC charge cord	080926-22062-1	22062
Steady Charge (SC) Plug-In Charger Holder	080926-90010-3	90010
AC Fast Charger/Holder*	080926-90011-0	90011
DC #1 Fast Charger/Holder*	080926-90012-7	90012
DC #2 Fast Charger/Holder*	080926-90013-4	90013
Lithium Ion Battery Pack	080926-90316-6	90316
Bank Charger (SC) 120V AC	080926-90400-2	90400
Bank Charger (SC) 230V AC	080926-90400-2	90400
Bank Charger 12V DC	080926-90600-6	90600
Alkaline battery carrier (Batteries not included)	080926-90542-9	90542
Survivor (Low Profile) Smoke Cutter Plug Kit	N/A	908019

\*Not shown

