

PN12C

MULTI-CONTACT CONNECTORS **GRP** OR **METAL** OR **STAINLESS STEEL**

16 A IP66/IP67



WALL MOUNTING SOCKET PN12C



Wall box poly 30°
511B3M20

Socket-outlet
01A4001

PLUG PN12C



Straight handle poly
511P0D18

Inlet
01A8001

MAIN FEATURES

Maximum voltage	480 V	Σ of currents (contacts)	≤ 110 A
Impulse withstand voltage	5 kV/Pollution degree 3	Flexible wiring (min-max)	1-2,5 mm ²
Contact resistance	< 2 mΩ	Wiring (terminals)	To weld/crimp
Permitted current range	4-20 mA/16 A	Keying positions	2
Rated current percontact (max)	16 A		

CLIMATIC FEATURES

Ambient temperature	-40 °C to +60 °C	Salt, Fog performance	1000 hours connected
IP protection plug connected	IP66/IP67	Resistance to fluids	Motor oils, petrol, oils, detergents...
IP protection lid closed	IP66/IP67		

MECHANICAL FEATURES

Butt contacts	Pastilles argent-nickel	Shock resistance (poly casing)	IK08
Contact protection	Silvering	Shock resistance (metal casing)	IK09
Load cycles	> 5000 cycles	Vibration	Frequency 5-1000 Hz, 1g/(90 minutes on each critical frequency) according to IEC 6068-2-6

i

AISI 304 stainless steel version available on request



SOCKET-OUTLET female
PN12C (16 A)



INLET male
PN12C (16 A)



GRP	480 V AC	12 contacts	01A4001	01A8001
METAL	480 V AC	12 contacts	09A4001	09A8001
		Bag of 13 contacts	01AA213	01AA113

► Each product is supplied with 1 bag of 13 contacts, supplied with insulation sleeves and ferrules

i

For a black colour GRP housing replace the second reference character 1 with 5.

INFO+

OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 94.

