



WALL MOUNTING SOCKET DN9c



Wall box metal 20°
593B2M25

Socket-outlet
1914081

PLUG DN9c



Straight handle poly
513POD30

Inlet
1918081

MAIN FEATURES

| | | | |
|--|---------|---------------------------|------------------------|
| Rated current/contact (wiring according to standard) | 30 A | Ambient temperature | -40°C to +60°C |
| Σ of currents (contacts) | ≤ 210 A | Flexible wiring (min-max) | 1-6 mm ² |
| Maximum voltage | 415 V | Stranded wiring (min-max) | 1,5-10 mm ² |
| IP protection lid closed | IP55 | Wiring (terminals) | screw-type |
| IP protection plug connected | IP54 | Keying positions | 2 |
| Shock resistance | IK09 | | |



In case of Different voltage, think of MARECHAL® keying position coding

SOCKET-OUTLET female DN9c (30 A)



INLET male DN9c (30 A)



| | | | |
|----------|------|---------|---------|
| 50 V AC | 6P | 1914060 | 1918060 |
| 50 V AC | 7P | 1914070 | 1918070 |
| 50 V AC | 8P | 1914080 | 1918080 |
| 50 V AC | 9P | 1914090 | 1918090 |
| 415 V AC | 5P+E | 1914051 | 1918051 |
| 415 V AC | 6P+E | 1914061 | 1918061 |
| 415 V AC | 7P+E | 1914071 | 1918071 |
| 415 V AC | 8P+E | 1914081 | 1918081 |

► The contacts can be assigned either power or signal.



INFO+

OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 94.