

PN7c

MULTI-CONTACT CONNECTORS

GRP

OR

METAL

25 A IP66/IP67



WALL MOUNTING SOCKET PN7c



Wall box poly 30°
511B3M20

Socket-outlet
01P4061

PLUG PN7c



Straight handle poly
511POD18

Inlet
01P8061

MAIN FEATURES

Rated current/contact (wiring according to standard)	25 A	Shock resistance (metal casing)	IK09
Σ of currents (contacts)	≤ 130 A	Ambient temperature	-40 °C to +60 °C
Maximum voltage	500 V	Flexible wiring (min-max)	1-4 mm ²
IP protection lid closed	IP66/IP67	Stranded wiring (min-max)	1-6 mm ²
IP protection plug connected	IP66/IP67	Wiring (terminals)	screw-type
Shock resistance (poly casing)	IK08	Keying positions	5



In case of Different voltage, think of MARECHAL® keying position coding



SOCKET-OUTLET female
PN7c (16/25 A)



INLET male
PN7c (16/25 A)



50 V AC	6P (16 A)	01P4060	01P8060
50 V AC	7P (16 A)	01P4070	01P8070
500 V AC	5P+E (25 A)	01P4051	01P8051
500 V AC	6P+E (16 A)	01P4061	01P8061



For a black colour GRP housing replace the second reference character 1 with 5.



SOCKET-OUTLET female
PN7c (16/25 A)



INLET male
PN7c (16/25 A)



50 V AC	6P (16 A)	09P4060	09P8060
50 V AC	7P (16 A)	09P4070	09P8070
415 V AC	5P+E (25 A)	09P4051	09P8051
415 V AC	6P+E (16 A)	09P4061	09P8061



INFO+

OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 94.